## **Amendments to the Claims**

This listing of claims will replace all prior versions and listings of claims in the application:

## **Listing of Claims:**

Claims 1-12 (cancelled)

Claim 13 (currently amended): A method for purifying a gas stream containing at least hydrogen (H<sub>2</sub>), carbon monoxide (CO), at least one metal carbonyl\_and at least one impurity selected from oxygen (O<sub>2</sub>) and unsaturated hydrocarbons, in which:

- (a) the gas stream is contacted with a second adsorption bed to adsorb at least one metal carbonyl, thereby resulting in a partially purified gas stream, and
- (b) said partially purified gas stream is contacted with a first catalyst bed comprising at least one catalyst containing copper, in order to convert at least part of the oxygen and at least one unsaturated hydrocarbon present in the gas stream to one or more catalysis products, at a temperature of between 100°C and 200°C and at a pressure of at least 10 bar, thereby producing a further purified gas stream.

Claim 14 (previously presented) The method of claim 13, wherein the temperature is between 120°C and 180°C and/or the pressure is between 10 and 18 bar.

Claim 15 (previously presented) The method of claim 13, wherein said first catalyst bed and said second adsorption bed have an hourly space velocity, and wherein said gas hourly space velocity is between 1000 and 10000 Sm<sup>3</sup>/h/m<sup>3</sup>.

Claim 16 (currently amended) The method of claim 13, wherein the gas stream containing at least hydrogen (H<sub>2</sub>), carbon monoxide (CO), at least one metal carbonyl and at least one impurity selected from oxygen (O<sub>2</sub>) and unsaturated hydrocarbons also contains one or more organosulfur, organonitrogen and/or organochlorine compounds, and in that:

- (a') (c) the further partially purified gas stream is contacted with a second catalyst bed to convert at least part of the organosulfur, organonitrogen and/or organochlorine compounds to organic compounds and to polar inorganic compounds, thereby producing a refined gas stream; and
- (a") (d) the refined gas stream is contacted with a third adsorption bed to adsorb at least part of the inorganic compounds produced in step (c), thereby producing an incompletely purified gas stream,
- (b) said incompletely purified gas stream is contacted with a first catalyst bed comprising at least one catalyst containing copper, in order to convert at least part of the oxygen and at least one unsaturated hydrocarbon present in the gas stream to one or more catalysis products, at a temperature of between 100°C and 200°C and at a pressure of at least 10 bar, thereby producing a further purified gas stream.

Claim 17 (currently amended) The method of claim 13, wherein, prior to step (a), the a raw gas stream containing at least hydrogen (H<sub>2</sub>), carbon monoxide (CO), at least one metal carbonyl and at least one impurity selected from oxygen (O<sub>2</sub>) and unsaturated hydrocarbons also contains HCN impurities and/or at least one compound of an element selected from the group formed by mercury, sulfur, chlorine, arsenic, selenium, bromine and germanium, and in that:

(e) said further purified raw gas stream is contacted with the a first adsorption bed to adsorb at least part of the HCN impurities and/or at least one compound of at least one element selected from the group formed by mercury, sulfur, chlorine, arsenic, selenium, bromine and germanium, thereby producing the gas stream which enters step (a).

Claim 18 (previously presented) The method of claim 13, wherein the gas stream containing at least hydrogen ( $H_2$ ), carbon monoxide (CO), at least one metal carbonyl and at least one impurity selected from oxygen ( $O_2$ ) and unsaturated hydrocarbons also contains at least one nitrogen oxide ( $NO_x$ ), and in that:

(f) said further purified\_gas stream is contacted with a third catalyst bed to convert at least one nitrogen oxide present in the gas stream.

Claim 19 (previously presented) The method of claim 18, wherein steps (b) and (f) are distinct.

Claim 20 (previously presented) The method of claim 18, wherein steps (b) and (f) are combined.

Claim 21 (previously presented) The method of claim 13, wherein in step (b), at least part of the oxygen and/or at least one unsaturated hydrocarbon are converted to catalysis products selected from water vapor (H<sub>2</sub>O), carbon dioxide (CO<sub>2</sub>) and/or alkanes.

Claim 22 (previously presented) The method of claim 13, wherein the gas stream to be separated contains 10% by volume to 90% by volume of  $H_2$ , 10% by volume to 90% by volume of CO and, optionally, methane.

Claim 23 (previously presented) The method of claim 18, wherein the gas stream issuing from one or the other of steps (b) or (f) is contacted with a fourth adsorption bed to remove H<sub>2</sub>O and/or CO<sub>2</sub> and/or optionally CH<sub>3</sub>OH and/or hydrocarbons formed during the passages over the catalyst beds, and/or a scrubbing step to remove the CO<sub>2</sub> and/or the methanol therein, particularly an amine scrub.

Claim 24 (previously presented) The method of claim 13, wherein the gas stream is subjected to at least one compression step upstream of step (b) and in which all or part of the heat generated by the compression of the stream is used to reach the desired temperature.